



e-VLBI activities in China

*Shanghai Astronomy Observatory
Chen Zhong*

*Third International VLBI Technology Workshop
Groningen, 10-13, Nov. 2014*



Contents



- ❖ **CVN e-VLBI network**
- ❖ **e-VLBI in Chang'E mission**
- ❖ **Demo of IPv6-based e-VLBI**
- ❖ **Network testing to Malaysia**
- ❖ **Conclusion**



CVN e-VLBI Network



❖ Stations

- Sh – Shanghai Sheshan, 25m, 1987
- Ur – Urumuqi, 25m, 1993
- Bj – Miyun, 50m, 2006
- Km – Kunming, 40m, 2006
- Tm – Tianma, 65m, 2013

❖ Data Center

- Shanghai new VLBI data center, 2013

❖ CVN e-VLBI Applications

- Chinese Lunar Exploration Project Phase I&II&III
- e-EVN, INT3, CMONOC



CVN e-VLBI Sites View



Ur, XAO



VLBI C&C Hall
ShAO



Bj, NAOC



Km, NAOC




Sh, NAOC



Tm, ShAO





CVN e-VLBI CSTNET Network BW



CSTNET: China Science and Technology Network, Chinese Academy of Sciences



CVN e-VLBI CSTNET Network BW



CSTNET: China Science and Technology Network, Chinese Academy of Sciences



e-VLBI for CLEP CE-3 missions




❖ Chinese Lunar Exploration Project Phase II(CE-3,2013)

◆ Service for measurement and control system

◆ Real-time Challenge

- VLBI Observation System: 10min->1min
- e-VLBI subsystem: 10 seconds, including failure recovery time



◆ Additional Function

- In data center, receiving & distributing
- Recording data



❖ Chinese Lunar Exploration Project Phase III(CE-5)

- ◆ CE-5T1: 64Mbps/stations(Nov, 2014-Now)
- ◆ CE-5: 128Mbps/stations(2017~2018)



CE-3 e-VLBI Network Link



❖ Data Rate


- CE-3: 32Mbps/station -> 64Mbps/station, 5 stations
- CE5-T1: 64Mbps/station, 4 stations
- CE5: 128Mbps/station, 4 stations+2 deep space stations

❖ Network Link Bandwidth

- Sh, Tm: $2 \times 1(10)$ Gbps Fiber
+100Mbps MSTP (China Telecom)
- Km, Ur: 155Mbps SDH(China Unicom)
+155Mb SDH(China Telecom)
- Bj: 155Mbps SDH(China Telecom)
+155Mb SDH(China Telecom)
- Utilization: >92%
- Cost: ~8k \$/month



CE-3 e-VLBI Network Topology





CE-3 e-VLBI Network Reliability Design



❖ Network Backup Solutions

◆ Requirement

- e-VLBI subsystem < 6 seconds
- Network link/router failure switch time < 2 seconds

❖ Layer 3

◆ Stations: Bj, Km, Ur with SDH link

◆ OSPF (Open Shortest Path First) Protocol

- Detect link failure and recovery time : ~10s

◆ +BFD(Bidirectional Forwarding Detection)

- Detect link failure and recovery time : ~1s

❖ Layer 2

◆ Stations: Sh, Tm with dedicated fiber link




e-VLBI CE-3 Network Topology



❖ Km, Ur, Bj

- Long Range Network
- Backbone unscheduled network situation:
Link down, routing and router switch to backup without informed
- Reliability Design play an important role for uninterrupted transfer
- Open Shortest Path First Interior Gateway Protocol/Bidirectional Forwarding Detection





e-VLBI CE-3 Endpoints




❖ Stations

- CDAS
- Mark5B+ (2/station)
- Modified Mark5B+ software
- Two level buffer
 - Amazon card & software

❖ Data center: DDU

- Cost Servers (5+1)+DAS
- Data Receiving
- Data Distribution




❖ Protocol: TCP(UDP)

❖ Control

- Script Control
- Start all station¢er software in one bash script, or separately
- Auto read skd file & set parameter, fast pause and restart running







e-VLBI tracking mission Netflow



❖ e-VLBI

Tree:All Traffic Summary



Graph Filters





Presets: Custom From: 2014-10-28 08:30 To: 2014-10-28 22:00 1 Day Refresh Clear

Search: Graphs per Page: 10 Thumbnails: Go Clear

CE-5T1

Showing All Graphs

Tree:All Traffic Summary





e-VLBI IPv6 Demo



❖ CNGI-IPv6 Network

◆ Background


- CNGI: Chinese Next Generation Internet
- Participation: Universities, Institutes, Companies
- Target: Demonstrate and Advance IPv6 network service
- e-VLBI by IPv6

◆ Jobs

- IPv6 network infrastructure construction
- Software modification to utilize IPv6
- Testing & Demonstration
- VLBI Data Center, Sh, Tm, Ur, Km



CVN e-VLBI IPv6 Connectivity





Station IPv6 Connectivity



❖ CNGI-IPv6 e-VLBI Infrastructure

- Sh、Tm、VLBI Center support IPv6
 - Bandwidth: 10Gbps
 - Sh,Tm → VLBI Center Bench
 - VLBI Center → CSTNET Beijing Bench
- VLBI Data Center - Beijing CSTNET IPv6
 - BW: 1024Mbps
 - **Free use!** 😊
- Km IPv6 BW: ~ 50 Mbps 😞
- Ur IPv6 BW: ~ 10 Mbps 😞
- Km,Ur can apply for more bandwidth, but budget...





IPv6 e-VLBI Testing



❖ Tm Observation Test


Real-time Netflow



Zero Baseline Testing



IPv6-based Station Webcam



VIVOTEK

视频流 1

数字输出 1 On Off

数字输出 2 On Off

← 缩放 +

← 调焦 +

Pan Stop Patrol

平移速度 0

俯仰速度 0

放大速度 0

对焦速度 0

客户端设置

配置

语言

Powered by VIVOTEK

上海佘山25米射电望远镜

2001:cc0:a014:99::(TCP-V) 2012/12/8 12:23:37

定位 -- 选择一项 --

VIVOTEK

视频流 1

数字输出 1 On Off

数字输出 2 On Off

← 缩放 +

← 调焦 +

Pan Stop Patrol

平移速度 0

俯仰速度 4

放大速度 5

对焦速度 5

客户端设置

配置

语言

Powered by VIVOTEK

上海天马山65米射电望远镜

2001:cc0:a014:99::(TCP-AV) 2012/12/8 12:21:01

定位 -- 选择一项 --

SUPREME

视频流 1

数字输出 1 On Off

数字输出 2 On Off

← 缩放 +

← 调焦 +

Pan Stop Patrol

平移速度 2

俯仰速度 0

放大速度 0

对焦速度 0

客户端设置

配置

语言

Powered by VIVOTEK

昆明40米射电望远镜

2400:dd07:1004:7::(TCP-V) 2012/12/8 12:36:57

定位 -- 选择一项 --

SUPREME

视频流 1

数字输出 1 On Off

数字输出 2 On Off

← 缩放 +

← 调焦 +

Pan Stop Patrol

平移速度 2

俯仰速度 2

放大速度 4

对焦速度 0

客户端设置

配置

语言

Powered by VIVOTEK

中科院新疆天文台—南山基地

2400:dd0c:1003:1::(TCP-AV) 2012/12/8 14:49:45

定位 -- 选择一项 --







e-VLBI ABC TCP protocol



❖ Shared Internet for e-VLBI

- Bandwidth congestion and utilization
- VLBI stable raw data rate
- Done by CSTNET & ShAO
- ABCTCP
 - Closed-loop control TCP, desired speed as parameter
 - Testing between ShAO-CSTNET(Beijing)Backbone Network







e-VLBI ABC TCP protocol



Average throughput




The Standard Deviation in Transferring 2GB File



5 times based standard deviation




e-VLBI ABC TCP protocol



Desired Transfer Speed Testing



Networking between China-Malaysia



❖ Background

- Proposing a new VLBI station in Malaysia

❖ Organization

- 1) Malaysia Putra University
- 2) University of Malaya

❖ Network


- MyREN – TEIN - CSTNET

❖ Network Testing tools

- Iperf TCP&UDP/FTP/UDT/ Tsunami-UDP



❖ staff

- Lim Yang Wei^{1,2}, Chen Zhong, Zamri Zainal Abidin², Shaiful Jahari Hashim²





China-Malaysia Networking Testing



| Protocol | File sizes (bytes) | Speed (Mbps) | Time (s) | Packet loss (%) |
|-------------|--------------------|--------------|----------|-----------------|
| FTP | 536870912 | 82.96 | 50.56 | 0% |
| | 1073741824 | 91.98 | 102.32 | 0% |
| Tsunami-UDP | 536870912 | 83.93 | 48.8 | 0% |
| | 1073741824 | 84.80 | 96.6 | 0% |
| UDT | 536870912 | 72.19 | 59.49 | 0% |
| | 1073741824 | 78.45 | 109.49 | 0% |



New VLBI Center



Command&Control Hall



Main Server Room



Systems in New VLBI Center



❖ Computing system

- Software correlator(384 Xeon E5 cores, 2.4G, DAS 72TB)
- DiFX: 48+16 cores, 50TB, 6 Mark5
 - Haswell 2.6G, 400 cores, 360TB
- Post processing/Orbit/Positoin/

❖ Storage

- Raw data storage: 300TB
- Results data storage: 30TB

❖ Networking

- 10Gb Ethernet Intranet
- 40Gb Infiniband interconnection in software correlator cluster

❖ Distributed LED Display Wall

❖ IP-based Voice Command System

❖ Power and Cooling

- UPS: backup support > 2hours





Mark5/6 System@Center



❖ Mark5/6

- **4 Mark5A, 8 Mark5B, 3 Mark5B+, 1 Mark5C, 1 Mark6**
- **Disk Modules: 180**
- **Firmware/Software upgrade, all Mark5@stations and center**


| | | SN | Type | Card Type | Kernel | Mark5 | Streamstor SDK | Firmware | Driver |
|----|------|------------|---------|-------------|------------------|-------|----------------|----------|--------|
| 1 | CLEP | Mark5-818 | Mark5B+ | PCI-816VXF2 | 2.6.18-6-686 4.0 | 2.2.3 | 9.2.1 | 16.31 | 1031 |
| 2 | | Mark5-811 | Mark5B+ | AMAZON-VP | 2.6.18-6-686 4.0 | 2.2.2 | 9.2.1 | 16.31 | 1031 |
| 3 | | Mark5-814 | Mark5B+ | AMAZON-VP | 2.6.18-6-686 4.0 | 2.2.1 | 9.2.1 | 16.31 | 1031 |
| 4 | | Mark5-653 | Mark5B | AMAZON-VP | 2.6.18-6-686 4.0 | 2.2.1 | 9.2.1 | 16.31 | 1031 |
| 5 | | Mark5-687 | Mark5B | AMAZON-VP | 2.6.18-6-686 4.0 | 2.2.1 | 9.2.1 | 16.31 | 1031 |
| 6 | | Mark5-697 | Mark5B | AMAZON-VP | 2.6.18-6-686 4.0 | 2.2.1 | 9.2.1 | 16.31 | 1031 |
| 7 | | Mark5-785 | Mark5B | AMAZON-VP | 2.6.18-6-686 4.0 | 2.2.1 | 9.2.1 | 16.31 | 1031 |
| 8 | | Mark5-636 | Mark5B | AMAZON-VP | 2.6.18-6-686 4.0 | 2.2.1 | 9.2.1 | 16.31 | 1031 |
| 9 | | Mark5-739 | Mark5B | PCI-816VXF2 | 2.6.18-6-686 4.0 | 2.2.1 | 9.2.1 | 16.31 | 1031 |
| | | | | | | | | | |
| 10 | DiFX | Mark5-643 | Mark5B | PCI-816VXF2 | 2.6.18-6-686 4.0 | 2.2.1 | 9.2.1 | 16.31 | 1031 |
| 11 | | Mark5-685 | Mark5A | PCI-816VXF2 | 2.6.18-6-686 4.0 | 2.2.1 | 9.2.1 | 13.04 | 1031 |
| 12 | | Mark5-635 | Mark5A | PCI-816VXF2 | 2.6.18-6-686 4.0 | 2.2.1 | 9.2.1 | 13.04 | 1031 |
| 13 | | Mark5-738 | Mark5B | AMAZON-VP | 2.6.18-6-686 4.0 | 2.2.1 | 9.2.1 | 16.31 | 1031 |
| 14 | | BR-RS-8237 | Mark5A | PCI-816VXF2 | 2.6.18-6-686 4.0 | 2.2.1 | 9.2.1 | 13.04 | 1031 |
| 15 | | Mark5-646 | Mark5A | PCI-816VXF2 | 2.6.18-6-686 4.0 | 2.2.1 | 9.2.1 | 13.04 | 1031 |



Conclusion



- ❖ **Space mission continuous support**
 - CLEP Phase III, CE-5 mission
 - Deep space explorations: Mars, ...
- ❖ **Shanghai Correlator Center**
 - Real time data transmission
 - e-Transfer
- ❖ **Bandwidth and Cost**
 - Win-win cooperation with CSTNET to get more support
 - IPv6 interested by anyone ?



Thank 😊